

**§ 64.2201 Scope.**

The definitions included in this subpart shall be used solely for the purpose of implementing CALEA requirements.

**§ 64.2202 Definitions.**

*Call identifying information.* Call identifying information means dialing or signaling information that identifies the origin, direction, destination, or termination of each communication generated or received by a subscriber by means of any equipment, facility, or service of a telecommunications carrier. Call identifying information is “reasonably available” to a carrier if it is present at an intercept access point and can be made available without the carrier being unduly burdened with network modifications.

*Collection function.* The location where lawfully authorized intercepted communications and call-identifying information is collected by a law enforcement agency (LEA).

*Content of subject-initiated conference calls.* Capability that permits a LEA to monitor the content of conversations by all parties connected via a conference call when the facilities under surveillance maintain a circuit connection to the call.

*Destination.* A party or place to which a call is being made (e.g., the called party).

*Dialed digit extraction.* Capability that permits a LEA to receive on the call data channel a digit dialed by a subject after a call is connected to another carrier’s service for processing and routing.

*Direction.* A party or place to which a call is re-directed or the party or place from which it came, either incoming or outgoing (e.g., a redirected-to party or redirected-from party).

*IAP.* Intercept access point is a point within a carrier’s system where some of the communications or call-identifying information of an intercept subject’s equipment, facilities, and services are accessed.

*In-band and out-of-band signaling.* Capability that permits a LEA to be informed when a network message that provides call identifying information (e.g., ringing, busy, call waiting signal, message light) is generated or sent by

the IAP switch to a subject using the facilities under surveillance. Excludes signals generated by customer premises equipment when no network signal is generated.

*J-STD-025.* The interim standard developed by the Telecommunications Industry Association and the Alliance for Telecommunications Industry Solutions for wireline, cellular, and broadband PCS carriers. This standard defines services and features to support lawfully authorized electronic surveillance, and specifies interfaces necessary to deliver intercepted communications and call-identifying information to a LEA.

*LEA.* Law enforcement agency; e.g., the Federal Bureau of Investigation or a local police department.

*Origin.* A party initiating a call (e.g., a calling party), or a place from which a call is initiated.

*Party hold, join, drop on conference calls.* Capability that permits a LEA to identify the parties to a conference call conversation at all times.

*Subject-initiated dialing and signaling information.* Capability that permits a LEA to be informed when a subject using the facilities under surveillance uses services that provide call identifying information, such as call forwarding, call waiting, call hold, and three-way calling. Excludes signals generated by customer premises equipment when no network signal is generated.

*Termination.* A party or place at the end of a communication path (e.g. the called or call-receiving party, or the switch of a party that has placed another party on hold).

*Timing information.* Capability that permits a LEA to associate call-identifying information with the content of a call. A call-identifying message must be sent from the carrier’s IAP to the LEA’s Collection Function within eight seconds of receipt of that message by the IAP at least 95% of the time, and with the call event time-stamped to an accuracy of at least 200 milliseconds.

[64 FR 51718, Sept. 24, 1999, as amended at 67 FR 22008, May 2, 2002]